

CMP9610

Wi-Fi 6 Performance with BLE & 802.15.4

Tri-Protocol industrial grade wireless for IoT

The CMP9610 delivers the performance and network optimization capabilities of Wi-Fi 6, which is critical for today's complicated and crowded wireless systems. Moreover, it offers flexibility to OEMs and users to leverage lower bandwidth and longer-range protocols to address applications that have their own unique needs. CEL is offering its solutions with an antenna connector, RF pin, and its high-performance PCB-trace antenna for use in harsh environments. With the ability to support Linux or RTOS systems, the CMP9610 is versatile and ready for integration with almost any MCU or MPU for a variety of applications.

WIRELESS FEATURES

- DB Wi-Fi 6, BT5.4, 802.15.4
- Interfaces: Wi-Fi-USB, BT-USB, 802.15.4-SPI
- Dual-Band 802.11 ax
 - Tx: +20 dBm
 - Single Stream: 20MHz Channels
- BLE 5.4
 - Tx: +4dBm (1M PHY)
 - 1/2Mbps, Coded PHY 500/125kbps
- AP, STA, Direct, Combination
- Long Range & Broad Coverage
- TWT
- WPA2/3 Security

ANTENNA OPTIONS

- Integrated Dual-Band PCB Trace
- MHF4 connector
- RF pin



- 2.4/5GHz
- Wi-Fi-USB, BT-USB, SPI
- PCB-trace Antenna or connector
- Castellation Edge Connector
- LGA option
- 12x12mm

EVALUATION PLATFORM

- USB Interface Board for Easy Evaluation and development

OTHER

- Certifications: FCC/IC/CE
- 16.64 x 27.80 x 3.47 mm, 12x12mm LGA
- Industrial Temperature: -40 C to +85 C Operation
- Castellation Edge Connections to HOST PCB

HOST DRIVER SOURCE CODE

- Linux/Android for MPU
 - Pre-tested and integrated in NXP's iMX 6/7/8/9 SDKs, Others MPUs supported
- FreeRTOS for MCU
 - Pre-tested and integrated in NXP's RT1170/1064/1060/1050/1024/1020 SDKs

TOOLS AND SUPPORT

- MCUXpresso IDE
- Documentation: Hardware Design Guide, Software QSG
- CEL Software Repository

APPLICATIONS

- Healthcare and Medical Devices
- Building Automation
- Retail/POS Terminals
- Security, Video/Cameras
- Smart Home

Questions? Call Us

(408) 919-2500

www.cel.com